

30M IR FIXED LENS BULLET CAMERA

I3-310IP04



1/3" CMOS Sensor
3 Mega-Pixel
True Day & Night (IR Cut Removable)
0 Lux (IR On) Min. Illumination
ONVIF

Digital WDR
3D Noise Reduction
Motion Detection and Privacy Masking
3.6mm Mega-Pixel Lens
30m IR Illumination

PoE Support
1 Way Audio
IP 66 Protection

Specifications

Camera	Video	Model	I3-310IP04
		Image Sensor	1/3" CMOS
		Effective Pixels	2048×1536
		Electronic Shutter	1/25s ~ 1/100000s
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		WDR Range	Digital WDR
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
		Video Compression	H.264
Compression		Resolution	3MP(2048×1536), 1080P(1920×1080), 720P(1280×720), D1, CIF, 480x240 3MP(1~30fps) / 1920x1080(1~30fps) / 1280x720(1~30fps)
		Multi-stream	D1(1~30fps) / CIF(1~30fps) / D1(1~30fps) / CIF(1~30fps) / 480x240(1~30fps)
		Bit rate	64Kbps ~ 8Mbps
		Encode Mode	VBR/CBR
		Image Quality	Five levels under VBR; Free adjustment under CBR

Housing	IR Distance	20-30m
	Lens	3.6mm
	Iris	Fixed Iris
	Lens Mount	Φ12 mount
	Water-proof	IP66
	Bracket	3-Axis Wall Bracket
Connectivity	Dimensions	Φ87mm×219mm
	Weight(gross)	621g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS 2.0 Control Software
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
Others	Ethernet	100Mbps
	PoE	Yes
	Power Supply	DC12V/PoE
	Work Environment	-10 C~50 C, 10%~90% Humidity

